



MOBILE HYDRAULIC POWER UNIT

MODEL HT74DVDQ

This Sound Attenuated power unit is designed to be used in residential areas and other locations where low sound levels are required. With an efficient Deutz diesel engine this unit meets today's emission standards and demanding hydraulic power requirements.

SPECIFICATIONS

ENGINE:..... Deutz TD 2.9 L4 (EPA Tier 4 Final)
HORSE POWER:..... 74 @ 2500 RPM
HYDRAULIC OUTPUT*:.....Variable Max 29 GPM (109 LPM)
OPERATING PRESSURE*:..... Maximum 2900 PSI (199 Bar)
HOSE PORT SIZE:..... Pressure 1" (25 mm)
Return 1 1/4" (31.75 mm)
Case Drain 1/2" (13 mm)
HYDRAULIC OIL:..... Chevron Clarity AW46
also: Biodegradable Oil (Consult Factory)
OIL FILTRATION:..... 10 Micron (Standard)
OIL RESERVOIR CAPACITY:..... 60 U.S. Gallons (227 Liters)
FUEL TANK CAPACITY:..... 115 U.S. Gallons (435 Liters)
FUEL CONSUMPTION:..... Approx. 3.5 U.S. Gal/Hr (15.9 Liters/Hr)
NOISE LEVELS @ 2800 RPM: 85dB @ 3 Ft. (1M), 70dB @ 23 Ft. (7M)
DIMENSIONS :..... L 156" (396 cm), W 70" (178 cm), H 82" (208 cm)
WEIGHT (Dry):..... 4306 lbs. (1953 kg)

* For Flows and Pressures Other Than Standard, Consult Factory

Since we are constantly working to improve our products, specifications are subject to change without notice.



167 Stock Street, Nesquehoning, PA 18240 Phone: 570-645-3779 Fax: 570-645-4061

Website: www.hydra-tech.com

E-Mail: htpump@hydra-tech.com

Model HT75DVDQ

