

## PORTABLE HYDRAULIC POWER UNIT

### MODEL HT75DJV



This model features a John Deere 4 cylinder water cooled diesel with your choice of fixed displacement gear or pressure compensated piston hydraulic pumps. It is designed to drive our submersible pumps or other hydraulic equipment requiring flows to 40 GPM and pressures to 2500 PSI.

**Now Tier 4 Final  
Call for Details**

## FEATURES

- Dependable John Deere Diesel Engine
- Skid Frame Chassis with Built -In Fuel Tank and Fork Lift Slots
- Automatic Engine Safety Shutdown Package
- Gear-Type Hydraulic Pump (HT75DJD)
- Pressure Comp. Piston Pump (HT75DJV)
- Spin-On Return Filter W/ Indicator
- Engine Mounted Hydraulic Oil Cooler
- System Relief Valve
- Made in USA
- Liquid Filled Pressure Gauge
- Fluid Level/ Temperature Gauge

### OPTIONS

- Highway Trailer
- Multiple Hydraulic Circuits
- Other Flow and Pressure Combinations
- Float Switch Control Operation

A0116

## Model HT75DJD/V Overall Dimensions

**Specifications below are correct**

### SPECIFICATIONS

ENGINE:.....John Deere Diesel (Tier 4 Final)  
HORSEPOWER:.....74 @ 2400RPM  
HYDRAULIC OUTPUT\*:.....Variable, Max. 40 GPM (151 LPM)  
OPERATING PRESSURE\*:.....Maximum 2500 PSI (170 Bar)  
HOSE PORT SIZE:.....1" or 1 1/4" NPT  
HYDRAULIC OIL:.....SAE 10W or 20W Type AW  
also:..... Biodegradable Oil (Consult Factory)  
OIL FILTRATION:.....10 Micron (Standard)  
OIL RESERVOIR CAPACITY:.....50 U.S. Gallons (189 Liters)  
FUEL TANK CAPACITY:.....TBD  
FUEL CONSUMPTION:.....Approx. 4.53 U.S. Gal/Hr (17.1 Liters/Hr)  
DIMENSIONS:.....TBD  
WEIGHT (Dry):.....TBD

\* For Flows and Pressures Other Than Standard, Consult Factory

Since we are constantly working to improve our products, specifications are subject to change without notice.



167 Stock Street, Nesquehoning, PA 18240 Phone: 570-645-3779 Fax: 570-645-4061

Website: [www.hydra-tech.com](http://www.hydra-tech.com)

E-Mail: [htpump@hydra-tech.com](mailto:htpump@hydra-tech.com)